

# USB 4K60 TYPE-C TO TYPE-C FLEX CABLE

The TiGHT AV USB-C Flex Series features premium Type-C to Type-C USB cables that provides data transfer rates of up to 20Gbps and enables users to connect laptops or other devices to USB-C peripherals. It supports various video standards, including DisplayPort, DisplayPort Alt mode, Thunderbolt, and USB4.

The cable is available in two configurations: one is a USB-C to USB-C male without a locking mechanism, while the other features a locking mechanism on one connector side to ensure secure connections in critical applications. The locking screw mechanism adheres to USB-IF standards and is compatible with a range of devices, including TiGHT AV USB-C devices that support locking connectors.

Supporting up to 240W charging power, this USB-C to USB-C cable complies with the latest USB-IF specifications for USB and PD 3.1 devices. It is ideal for charging your MacBook, Chromebook, gaming laptop, iPad, and other high-powered USB-C devices with a robust cable that ensures safe and efficient charging speeds.

This cable series is ideal for various applications, including conference rooms, educational presentations, and workstations in both office and home environments.

### **PRODUCT RANGE**

#### USBC-M/MLOCK-FLEX



USBC-M/MLOCK-FLEX-2

USBC-M/MLOCK-FLEX-1 USB-C 4K60 FLEX CABLE WITH LOCKING CONNECTOR- 1M USB-C 4K60 FLEX CABLE WITH LOCKING CONNECTOR- 2M

### USBC-M/M-FLEX



USBC-M/M-FLEX-1 USBC-M/M-FLEX-2

USB-C 4K60 FLEX CABLE- 1M USB-C 4K60 FLEX CABLE- 2M

### **KEY FEATURES**

- USB 20Gbps (USB 3.2 Gen 2x2)
- Full Featured USB-C (M) to USB-C (M) Cable
- Supports PD 3.1 with up to 240W of charging power.
- E-Marker Chipset
- 1/2/4 Lane Displayport Alt mode support
- Thunderbolt 3/4 and USB4 20Gbps support
- USB backward compatibility
- The M/MLOCK model features a screw locking mechanism that meets USB-IF standards for secure connections
- Available in lengths of: 1m and 2m

# **TIGHT POLICY**



Faulty product - minimal down time.

Up until six months after purchase, TiGHT AV will replace your product in advance of return of faulty product.

Your investment - built to last.

This TiGHT AV product come with a life time limited warranty.




### **SPECIFICATIONS**

| USB                   |  |
|-----------------------|--|
| USB Specification:    | USB 20Gbps, USB 10Gbps, 3.0, 2.0, 1.1 Compatible                       |
| Max Data Speed:       | 20Gbps (2x10Gbps)  |
| Video Support:        | DisplayPort Alt mode (1,2 or 4 Lanes),<br>Thunderbolt 3/4, DisplayLink |
| PHYSICAL              |  |
| Type:                 | Full Featured USB-C Male to USB-C Male                                 |
| Connector over mold:  | PVC  |
| Connector inner mold: | LD-PE  |
| CONDUCTORS            |  |
| Material:             | Tinned Copper  |
| Conductors:           | 30AWG (0.28/1)   |
| Wire Specification:   | (30AWG(0.28/1)*1P+DAM)*4P+32AWG*1P+32AW<br>G*4C+22AWG*2C+E+AEB         |
| SCREENING             |  |
| Type:                 | Triple shielding   |
| METAL SHELL SHIELDIN  | G  |
| Type:                 | Nickel plated metal can  |
| JACKET                |  |
| Color:                | Black  |
| Diameter:             | 5.6mm ± 0.25mm   |
| Material:             | PVC  |

| MECHANICAL             |  |
|------------------------|--|
| Cable Bending Radius:  | 45mm   |
| ELECTRICAL             |  |
| Temperature Rating:    | 80°C   |
| Storage Temperature:   | (-)20-80°C                                       |
| Voltage Rating:        | 30V  |
| Conductor Resistance:  | 381Ω/KM  |
| Insulation Resistance: | >100ΜΩ   |
| POWER                  |  |
| Maximum Power Delivery | 240W (PD3.1)                                     |
| Maximum Current:       | 5A   |
| E-Marker Chip:         | HUSB332B, Hynetek Semiconductor                  |
| STANDARDS COMPLIANC    | E  |
| Safety:                | PVC UL VW-1                                      |
| Environmental:         | RoHS, REACH, WEEE                                |
| Compliance:            | CE   |
| MODELS                 |  |
| USBC-M/MLOCK-FLEX-1    | USB-C 4K60 FLEX CABLE WITH LOCKING CONNECTOR-1M  |
| USBC-M/MLOCK-FLEX-2    | USB-C 4K60 FLEX CABLE WITH LOCKING CONNECTOR- 2M |
| USBC-M/M-FLEX-1        | USB-C 4K60 FLEX CABLE- 1M                        |
| USBC-M/M-FLEX-2        | USB-C 4K60 FLEX CABLE- 2M                        |

### **DIMENSIONS**



## **KEY FEATURES**

- USB 20Gbps (USB 3.2 Gen 2x2)
- Full Featured USB-C (M) to USB-C (M) Cable
- Supports PD 3.1 with up to 240W of charging power.
- E-Marker Chipset
- 1/2/4 Lane Displayport Alt mode support
- Thunderbolt 3/4 and USB4 20Gbps support
- USB backward compatibility
- The M/MLOCK model features a screw locking mechanism that meets USB-IF standards for secure connections
- Available in lengths of: 1m and 2m

### **TIGHT POLICY**



Faulty product - minimal down time.

Up until six months after purchase, TiGHT AV will replace your product in advance of return of faulty product.

Your investment - built to last.

This TiGHT AV product come with a life time limited warranty.

